



# SPECIFICATION

**Shenzhen DreamLNK Technology Co., Ltd.**  
**深圳市骏晔科技有限公司**

## 2.4G Rubber Rod Wi-Fi Antenna

### Product Specification

Client Name		Frequency Band	2400MHz-2500MHz
Wire Name		Version	A1
Customer's Part Number		DreamLNK's Part Number	W10
RF Designer	James Wang	RF Manager	Knight Ai
Structural Designer		Structural Design Manager	
Technical Director		Date	2016-03-12

Client confirmation:

Whether the product meets your requirements?  OK  NG

# Contents

Cover .....	1
Contents .....	2
1. Photos .....	3
2. Parameters .....	3
3. S11 Data .....	4
4. Structure diagram .....	5
5. Environmental reliability experiment report .....	6
6. Connector BOM .....	6
7. Contact us .....	7

The information provided by us should be kept strictly confidential, and it is not allowed to disclose to anyone else or other companies, without prior written consent

---

## 1. Photos




## 2. Parameters

Test parameters			
Product Name	2.4G Rubber Rod Antenna	Model No	W10
Electrical Specifications			
Frequency Range	2400-2500MHz	Polarization	Vertical
Input Impedance	50 $\Omega$	Radiation direction	Omnidirectional
VSWR	$\leq 1.5$	Power Capacity	50W
Gain	3dBi	Bandwidth	135/46MHz
Mechanical Specifications			
Dimensions	10.5cm	Color	Black
Connector Model	SMA male	Cable Length	3000 $\pm$ 3mm
Antenna Material	ABS		
Working Temperature	-30 $^{\circ}$ C--+65 $^{\circ}$ C	Relative Humidity	40~85%

The information provided by us should be kept strictly confidential, and it is not allowed to disclose to anyone else or other companies, without prior written consent

### 3. S11 Data (VSWR, Return loss, Smith)



The information provided by us should be kept strictly confidential, and it is not allowed to disclose to anyone else or other companies, without prior written consent

#### 4. Structure diagram

1	2	3	4	5	6	7	8																																								
						<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">标记</td> <td style="width: 20%;">姓名</td> <td style="width: 20%;">职位内容</td> <td style="width: 20%;">日期</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>		标记	姓名	职位内容	日期																																				
标记	姓名	职位内容	日期																																												
						<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20%;">No.</td> <td style="width: 20%;">Part Number</td> <td style="width: 20%;">Name</td> <td style="width: 20%;">Material</td> <td style="width: 20%;">Qty</td> </tr> <tr> <td>1</td> <td>HX-ANS7-03</td> <td>塑胶本体</td> <td>TPE 黑色</td> <td>1</td> </tr> <tr> <td>2</td> <td>HX-ANS7-02</td> <td>连接筒</td> <td>PA-6 黑色</td> <td>1</td> </tr> <tr> <td>3</td> <td>HX-ANS7-01</td> <td>定位柱</td> <td>PA-6 黑色</td> <td>1</td> </tr> <tr> <td>4</td> <td>HX-AND1-1213Z</td> <td>SMA 公头公针</td> <td>铜 镀镍</td> <td>1</td> </tr> <tr> <td>5</td> <td>SMA260-ZIGARRANT</td> <td>线材</td> <td>黄铜 Ø1.0*2.3mm</td> <td>1</td> </tr> <tr> <td>6</td> <td>HX-AND104-05</td> <td>铜管</td> <td>RG178 L=85.00mm</td> <td>1</td> </tr> <tr> <td>7</td> <td>HX-RG-78U</td> <td>线材</td> <td>黄铜 Ø1.0*2.3mm</td> <td>1</td> </tr> </table>		No.	Part Number	Name	Material	Qty	1	HX-ANS7-03	塑胶本体	TPE 黑色	1	2	HX-ANS7-02	连接筒	PA-6 黑色	1	3	HX-ANS7-01	定位柱	PA-6 黑色	1	4	HX-AND1-1213Z	SMA 公头公针	铜 镀镍	1	5	SMA260-ZIGARRANT	线材	黄铜 Ø1.0*2.3mm	1	6	HX-AND104-05	铜管	RG178 L=85.00mm	1	7	HX-RG-78U	线材	黄铜 Ø1.0*2.3mm	1
No.	Part Number	Name	Material	Qty																																											
1	HX-ANS7-03	塑胶本体	TPE 黑色	1																																											
2	HX-ANS7-02	连接筒	PA-6 黑色	1																																											
3	HX-ANS7-01	定位柱	PA-6 黑色	1																																											
4	HX-AND1-1213Z	SMA 公头公针	铜 镀镍	1																																											
5	SMA260-ZIGARRANT	线材	黄铜 Ø1.0*2.3mm	1																																											
6	HX-AND104-05	铜管	RG178 L=85.00mm	1																																											
7	HX-RG-78U	线材	黄铜 Ø1.0*2.3mm	1																																											
						<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;"> </td> <td colspan="2" style="text-align: center;"> <b>深圳市骏晖科技有限公司</b> </td> </tr> <tr> <td style="width: 20%;">项目名称</td> <td style="width: 20%;">日期</td> <td style="width: 20%;">设计/制图</td> <td style="width: 20%;">审核/批准</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td style="width: 20%;">产品名称</td> <td style="width: 20%;">规格</td> <td style="width: 20%;">比例</td> <td style="width: 20%;">版本</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td style="width: 20%;">产品型号</td> <td style="width: 20%;">数量</td> <td style="width: 20%;">日期</td> <td style="width: 20%;">版本</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>				<b>深圳市骏晖科技有限公司</b>		项目名称	日期	设计/制图	审核/批准					产品名称	规格	比例	版本					产品型号	数量	日期	版本																
		<b>深圳市骏晖科技有限公司</b>																																													
项目名称	日期	设计/制图	审核/批准																																												
产品名称	规格	比例	版本																																												
产品型号	数量	日期	版本																																												

The information provided by us should be kept strictly confidential, and it is not allowed to disclose to anyone else or other companies, without prior written consent

---

**Note:** The antenna design process needs to consider the placement position, angle, distance/ height (from the floor and from the PCB substrate), which is highly related to the product shape and structure, the position of the RF module signal input and output interface, as well as the position of the interference source inside the product etc.

The  $\pi$ -type network is reserved to match the antenna. When debugging the antenna, be sure to provide the entire product casing and internal PCBA function board, please also take into account external interference sources and parasitic capacitance, so that the antenna achieves the best performance index and working efficiency.

The above picture is just FYI. The PCB trace of the matching network refers to the 0.5mm line width, and the grounding on both sides of the network refers to the 0.35mm pitch to maintain good impedance characteristics.

If you have any questions, please send PCB documents to this e-mail [support@dreamlnk.com](mailto:support@dreamlnk.com)

## 5. Environmental reliability experiment report

Item	Test condition	Specification
Storage environment	Tested temperature, humidity and air pressure as following without specifying: 1. The temperature is $-30\text{ }^{\circ}\text{C} \sim +80\text{ }^{\circ}\text{C}$ 2. Relative humidity is 45% -85% 3. The air pressure is 86kpa-106kpa	The electrical mechanical performance is normal
High and low temperature test	Perform 5 cycles between $70\text{ }^{\circ}\text{C}$ and $40\text{ }^{\circ}\text{C}$ , then check the appearance quality, under normal conditions 1-2H	The size should meet the requirements for mechanical and electrical performance
Resistant to constant heat and humidity	Test Relative humidity: $95 \pm 3\%$ , Test temperature: $40\text{ }^{\circ}\text{C}$ . After continuous 2H running, take out the sample, and measure its electrical properties within 5 minutes, put the sample in a normal condition for another 1-2H, check the appearance quality	The size should meet the standard, and meet for mechanical and electrical performance
Vibration test	Vibration frequency range 10-55HZ, displacement amplitude: 0.35MM, acceleration amplitude: 50.0M / S, frequency of sweeping cycle: 30 times	Normal electrical and mechanical performance
Drop test	1M high-altitude free fall 3 times, in the direction of mutually perpendicular axes	Normal electrical and mechanical performance

The information provided by us should be kept strictly confidential, and it is not allowed to disclose to anyone else or other companies, without prior written consent

---

## 6. Contact us

### Shenzhen DreamLnk Technology Co., Ltd

★ Data collection, Smart home, Internet of Things applications, Wireless remote control technology, Remote active RFID, Antennas ★

**Office Add.:** Room 603, Unit C, Zone A, Huameiju Business Center, Xihu Rd., Bao'an District, Shenzhen, Guangdong Province, China

**Factory Add.:** 5th Floor, Building B, Huazhi Innovation Valley, No. 7 Yuhua Street, 138 Industrial Zone, Tangxia Town, Dongguan, Guangdong Province, China

**TEL.:** +86-755-29369047

**FAX:** +86-755-27844601

**Mobile:** +86 13760215716

**Wechat:** wsj\_james

**E-mail:** [james@dreamlnk.com](mailto:james@dreamlnk.com)

**Web:** [www.iot-rf.com](http://www.iot-rf.com)